

Safety Data Sheet

sulphur dioxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: D-SO2-113

Issue date: 1/8/2015 Revision date: 1/5/2023 Supersedes version of: 12/4/2019 Version: 0.3

Danger



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : sulphur dioxide
SDS no : D-SO2-113
Other means of identification : sulphur dioxide
CAS-No. : 7446-09-5
EC-No. : 231-195-2
EC Index-No. : 016-011-00-9
REACH registration No : 01-2119485028-34
Chemical formula : SO₂

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : See the list of identified uses and exposure scenarios in the annex of the safety data sheet.
Perform risk assessment prior to use.

Uses advised against : Consumer use.
Attention: These products must not be applied to humans or animals unless they are expressly designated as medical or medicinal gases!
Uses other than those listed above are not supported, contact your supplier for more information on other uses.

1.3. Details of the supplier of the safety data sheet

Messer Industriegase GmbH GmbH
Messer- Platz 1
D - 65812 Bad Soden am Taunus
Germany
T 0049-(0)-6196 7760-200 - F 0049-(0)-6196 7760-280
SDB.de@messergroup.com - www.messer.de

1.4. Emergency telephone number

Emergency telephone number : Messer Produktionsgesellschaft Salzgitter GmbH +49 (0) 5341 21-9333, erreichbar
Montags 0:00 bis Sonntags 24:00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Gases under pressure : Liquefied gas	H280
Health hazards	Acute toxicity (inhalation:gas) Category 3	H331
	Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
	Serious eye damage/eye irritation, Category 1	H318

Safety Data Sheet

sulphur dioxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: D-SO2-113

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

GHS05

GHS06

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H314 - Causes severe skin burns and eye damage.
H280 - Contains gas under pressure; may explode if heated.
H331 - Toxic if inhaled.
EUH071 - Corrosive to the respiratory tract.

Precautionary statements (CLP)

- Prevention

P280 - Wear protective clothing, eye protection, face protection, protective gloves.
P271 - Use only outdoors or in a well-ventilated area.
P260 - Do not breathe gas, vapours.
P264 - Wash hands, forearms and face thoroughly after handling.

- Response

P321 - Specific treatment (see supplemental first aid instruction on this label).
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P310 - Immediately call a POISON CENTER, a doctor.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- Storage

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.

- Disposal considerations

P501 - Dispose of contents and container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal..

2.3. Other hazards

None.

The substance/mixture has no endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
sulphur dioxide	CAS-No.: 7446-09-5 EC-No.: 231-195-2 EC Index-No.: 016-011-00-9 REACH registration No: 01-2119485028-34	100	Press. Gas (Liq.), H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318

Name	Product identifier	Specific concentration limits
sulphur dioxide	CAS-No.: 7446-09-5 EC-No.: 231-195-2 EC Index-No.: 016-011-00-9 REACH registration No: 01-2119485028-34	(1 ≤C < 100) STOT SE 3, H335

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : Remove contaminated clothing. Drench affected area with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product.
Prolonged exposure to small concentrations may result in pulmonary oedema.
Material is destructive to tissue of the mucuous membranes and upper respiratory tract.
Cough, shortness of breath, headache, nausea.
See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.
Treat with corticosteroid spray as soon as possible after inhalation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None that are more hazardous than the product itself.

5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel
- : Act in accordance with local emergency plan.
 - Try to stop release.
 - Evacuate area.
 - Ensure adequate air ventilation.
 - Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
 - Stay upwind.
 - See section 8 of the SDS for more information on personal protective equipment
- For emergency responders
- : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
 - Use chemically protective clothing.
 - Monitor concentration of released product.
 - See section 5.3 of the SDS for more information.

6.2. Environmental precautions

- Reduce vapour with fog or fine water spray.
- Try to stop release.

6.3. Methods and material for containment and cleaning up

- Hose down area with water.
- Keep area evacuated and free from ignition sources until any spilled liquid has evaporated (ground free from frost).
- Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4. Reference to other sections

- See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Safe use of the product
- : Installation of a cross purge assembly between the container and the regulator is recommended.
 - Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service.
 - Avoid exposure, obtain special instructions before use.
 - The product must be handled in accordance with good industrial hygiene and safety procedures.
 - Only experienced and properly instructed persons should handle gases under pressure.
 - Consider pressure relief device(s) in gas installations.
 - Ensure the complete gas system was (or is regularly) checked for leaks before use.
 - Do not smoke while handling product.
 - Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
 - Avoid suck back of water, acid and alkalis.
 - Do not breathe gas.
 - Avoid release of product into work area.
 - Use only lubricants and sealings approved for the specific gas service.

Safety Data Sheet

sulphur dioxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: D-SO2-113

Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions.
- Do not allow backfeed into the container.
- Protect containers from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If user experiences any difficulty operating valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Keep container valve outlets clean and free from contaminants particularly oil and water.
- Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not remove or deface labels provided by the supplier for the identification of the content of the container.
- Suck back of water into the container must be prevented.
- Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

- Observe all regulations and local requirements regarding storage of containers.
- Containers should not be stored in conditions likely to encourage corrosion.
- Container valve guards or caps should be in place.
- Containers should be stored in the vertical position and properly secured to prevent them from falling over.
- Stored containers should be periodically checked for general condition and leakage.
- Keep container below 50°C in a well ventilated place.
- Store containers in location free from fire risk and away from sources of heat and ignition.
- Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

sulphur dioxide (7446-09-5)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Schwefeldioxid
AGW (OEL TWA) [1]	2.7 mg/m ³
AGW (OEL TWA) [2]	1 ppm
Peak exposure limitation factor	1(I)
Remark	AGS;Y
Regulatory reference	TRGS900

sulphur dioxide (7446-09-5)	
DNEL: Derived no effect level (Workers)	
Acute - local effects, inhalation	2.7 mg/m ³
Long-term - local effects, inhalation	2.7 mg/m ³

PNEC (Predicted No-Effect Concentration) : None established.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.
Product to be handled in a closed system.
Systems under pressure should be regularly checked for leakages.
Ensure exposure is below occupational exposure limits (where available).
Gas detectors should be used when toxic gases may be released.
Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection : Wear goggles and a face shield when transfilling or breaking transfer connections.
Standard EN 166 - Personal eye-protection - specifications.
Provide readily accessible eye wash stations and safety showers.
- Skin protection
 - Hand protection : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
Wear chemically resistant protective gloves.
Standard EN 374 - Protective gloves against chemicals.
Chloroprene rubber (CR).
Standard EN 511 - Cold insulating gloves.
 - Other : Keep suitable chemically resistant protective clothing readily available for emergency use.
Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals.
Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
Recommended: Filter E (yellow).
Gas filters do not protect against oxygen deficiency.
Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .
Keep self contained breathing apparatus readily available for emergency use.
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
- Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas
- Colour : Colourless.

Odour : Pungent.

Odour threshold is subjective and inadequate to warn of overexposure.

pH : If dissolved in water pH-value will be affected.

Melting point / Freezing point	: -75.5 °C -75.5 °C
Boiling point	: -10 °C
Flash point	: Not applicable for gases and gas mixtures.
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Vapour pressure [20°C]	: 3.3 bar(a)
Vapour pressure [50°C]	: 8.4 bar(a)
Density	: Not applicable
Vapour density	: Not applicable.
Relative density, liquid (water=1)	: 1.5
Relative density, gas (air=1)	: 2.3
Water solubility	: Completely soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: No reliable data available.
Particle characteristics	: Not applicable for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
Critical temperature [°C]	: 158 °C

9.2.2. Other safety characteristics

Molar mass	: 64 g/mol
Evaporation rate	: Not applicable for gases and gas mixtures.
Gas group	: Press. Gas (Liq.)
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

Reacts with water to form corrosive acids.
May react violently with alkalis.
Reacts with most metals in the presence of moisture, liberating hydrogen, an extremely flammable gas.
With water causes rapid corrosion of some metals.
Moisture.
For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Toxic if inhaled.
Delayed fatal pulmonary oedema possible.

LC50 Inhalation - Rat [ppm]	1260 ppm/4h
-----------------------------	-------------

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : No known effects from this product.

Germ cell mutagenicity : No known effects from this product.

Carcinogenicity : No known effects from this product.

Toxic for reproduction : Fertility : No known effects from this product.

Toxic for reproduction : unborn child : No known effects from this product.

STOT-single exposure : Severe corrosion to the respiratory tract at high concentrations.

STOT-repeated exposure : No known effects from this product.

Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : Classification criteria are not met.

EC50 48h - Daphnia magna [mg/l] : 89 mg/l

EC50 72h - Algae [mg/l] : 48.1 mg/l

LC50 96 h - Fish [mg/l] : No data available.

12.2. Persistence and degradability

Assessment : Not applicable for inorganic products.

12.3. Bioaccumulative potential

Assessment : Product is an inorganic gas with a low potential to bioaccumulate in aquatic species.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.
Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Endocrine disrupting properties

The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects : May cause pH changes in aqueous ecological systems.

Effect on the ozone layer : None.

Effect on global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.
Gas may be scrubbed in alkaline solution under controlled conditions to avoid violent reaction.
Ensure that the emission levels from local regulations or operating permits are not exceeded.
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.eu> for more guidance on suitable disposal methods.
Must not be discharged to atmosphere.
Return unused product in original container to supplier.
16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN
UN-No. : 1079

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : SULPHUR DIOXIDE
Transport by air (ICAO-TI / IATA-DGR) : Sulphur dioxide
Transport by sea (IMDG) : SULPHUR DIOXIDE

14.3. Transport hazard class(es)

Labelling



2.3 : Toxic gases.
8 : Corrosive substances.

Transport by road/rail (ADR/RID)

Class : 2
Classification code : 2TC
Hazard identification number : 268
Tunnel Restriction : C/D - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other carriage : Passage forbidden through tunnels of category D and E

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.3 (8)
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-U

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable
Transport by air (ICAO-TI / IATA-DGR) : Not applicable
Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.
Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : Forbidden.

Cargo Aircraft only : Forbidden.

Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None.

Other information, restriction and prohibition regulations : Ensure all national/local regulations are observed.
None.

Seveso Directive : 2012/18/EU (Seveso III) : Covered.

National regulations

Water hazard class (WGK) : 1 - Slightly hazardous to water

Kenn-Nr. : 416

Regulatory reference : National / local legislations :
Sec15 DE General.
Sec15 DE CMR Tox 1 2 3 STOT SE1.
Sec 15 DE BImSchV 12 .
Sec 15 DE BImSchV 4.
TA Luft.

15.2. Chemical safety assessment

A CSA has been carried out.

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 2020/878.

Safety Data Sheet

sulphur dioxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: D-SO2-113

Abbreviations and acronyms

- : ATE - Acute Toxicity Estimate
- CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
- REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
- EINECS - European Inventory of Existing Commercial Chemical Substances
- CAS# - Chemical Abstract Service number
- LC50 - Lethal Concentration to 50 % of a test population
- RMM - Risk Management Measures
- PBT - Persistent, Bioaccumulative and Toxic
- vPvB - Very Persistent and Very Bioaccumulative
- STOT- SE : Specific Target Organ Toxicity - Single Exposure
- CSA - Chemical Safety Assessment
- EN - European Standard
- UN - United Nations
- ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
- IATA - International Air Transport Association
- IMDG code - International Maritime Dangerous Goods
- RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
- WGK - Water Hazard Class
- STOT - RE : Specific Target Organ Toxicity - Repeated Exposure
- PPE - Personal Protection Equipment
- UFI : Unique Formula Identifier

Training advice

- : Users of breathing apparatus must be trained.
- Ensure operators understand the toxicity hazard.

Further information

- : Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).
- Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at <http://www.Eiga.eu> .

Full text of H- and EUH-statements	
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
EUH071	Corrosive to the respiratory tract.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

DISCLAIMER OF LIABILITY

- : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
- Details given in this document are believed to be correct at the time of going to press.
- Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Safety Data Sheet

sulphur dioxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: D-SO2-113

Annex to the safety data sheet

This Annex documents the Exposure Scenarios (ESs) related to the identified uses of the registered substance. The ESs detail protective measures for workers and the environment in addition to those described in sections 7, 8, 11, 12 and 13 of the SDS that are required to ensure that the potential exposure to workers and the environment remains within acceptable levels for each of the identified uses.

Table of contents of the Annex

Identified Uses	Es N°	Short title	Page
Formulation of mixtures in pressure receptacles	EIGA113-1	Industrial uses, closed contained conditions	13
Calibration of analysis equipment	EIGA113-1	Industrial uses, closed contained conditions	13
Transfilling in pressure receptacles	EIGA113-1	Industrial uses, closed contained conditions	13
Metal treatment	EIGA113-2	Industrial uses, closed and open conditions	17
Feedstock in chemical processes	EIGA113-2	Industrial uses, closed and open conditions	17
Glass coating	EIGA113-2	Industrial uses, closed and open conditions	17
Water treatment	EIGA113-2	Industrial uses, closed and open conditions	17
Lubrication of rollers in glass manufacture	EIGA113-2	Industrial uses, closed and open conditions	17
Resin curing	EIGA113-2	Industrial uses, closed and open conditions	17
Refilling of refrigeration equipment	EIGA113-3	Professional uses	21
Wine making	EIGA113-3	Professional uses	21

Exposure scenario

sulphur dioxide

Annex to the safety data sheet
Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

1. EIGA113-1: Industrial uses, closed contained conditions

1.1. Title section

Industrial uses, closed contained conditions

ES Ref.: EIGA113-1
Revision date: 10/1/2016

Processes, tasks, activities covered	Industrial uses, including product transfers and associated laboratory activities within different closed or contained systems
--------------------------------------	--

Environment	Use descriptors
CS01	

Worker	Use descriptors
CS02	
CS03	

Assessment method	MEASE
-------------------	-------

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure:

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)	
Regional use tonnage:	≤ 80000 t/yr
Emission Days (days/year)	365

Technical and organisational conditions and measures	
Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
No emissions to water. In case of emissions to water, pH impact on the receiving water should be avoided, e.g. by neutralizing the effluent	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant	
Not applicable as there is no release to wastewater	

Exposure scenario

sulphur dioxide

Annex to the safety data sheet
Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions

1.2.2. Control of worker exposure:

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

See section 8 of the SDS.

Other conditions affecting workers exposure

Indoor or outdoor use

1.2.3. Control of worker exposure:

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Exposure scenario

sulphur dioxide

Annex to the safety data sheet
Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures	
Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor or outdoor use	

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure:

1.3.2. Worker exposure:

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	

Exposure scenario

sulphur dioxide

Annex to the safety data sheet
Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Dermal - Acute - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Acute - Local - Inhalation	0.648 mg/m ³	Indoor or outdoor use	0.24

1.3.3. Worker exposure:

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Dermal - Acute - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Acute - Local - Inhalation	1.08 mg/m ³	Indoor or outdoor use	0.4

1.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

1.4.1. Environment

Guidance - Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
------------------------	---

1.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
-------------------	---

Exposure scenario

sulphur dioxide

Annex to the safety data sheet
Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

2. EIGA113-2: Industrial uses, closed and open conditions

2.1. Title section

Industrial uses, closed and open conditions

ES Ref.: EIGA113-2
Revision date: 10/1/2016

Processes, tasks, activities covered	Industrial uses, including product transfers and associated laboratory activities within closed or partially closed conditions
--------------------------------------	--

Environment	Use descriptors
CS01	

Worker	Use descriptors
CS02	
CS03	

Assessment method	MEASE
-------------------	-------

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure:

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)

Regional use tonnage:	≤ 80000 t/yr
Emission Days (days/year)	365

Technical and organisational conditions and measures

No emissions to water. In case of emissions to water, pH impact on the receiving water should be avoided, e.g. by neutralizing the effluent	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant

Not applicable as there is no release to wastewater

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS

Exposure scenario

sulphur dioxide

Annex to the safety data sheet
Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions

2.2.2. Control of worker exposure:

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

See section 8 of the SDS.

2.2.3. Control of worker exposure:

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Exposure scenario

sulphur dioxide

Annex to the safety data sheet
Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Technical and organisational conditions and measures	
Local exhaust ventilation - efficiency of at least [%]:	90
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374	Mandatory since the product is corrosive
Wear suitable working clothes	Personal protection measures have to be applied in case of potential exposure only.
Use suitable eye protection. Wear suitable face shield	Personal protection measures have to be applied in case of potential exposure only.
Face mask with an ABEK1 filter offering an assigned protection factor of 30	Personal protection measures have to be applied in case of potential exposure only.

Other conditions affecting workers exposure	
Indoor or outdoor use	

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure:

2.3.2. Worker exposure:

2.3.3. Worker exposure:

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Dermal - Acute - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	



Exposure scenario

sulphur dioxide

Annex to the safety data sheet

Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Acute - Local - Inhalation	1.08 mg/m ³	Indoor or outdoor use, With LEV90%	0.4
----------------------------	------------------------	------------------------------------	-----

2.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

2.4.1. Environment

Guidance - Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
------------------------	---

2.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
-------------------	---

Exposure scenario

sulphur dioxide

Annex to the safety data sheet
Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

3. EIGA113-3: Professional uses

3.1. Title section

Professional uses

ES Ref.: EIGA113-3
Revision date: 10/1/2016

Processes, tasks, activities covered	Professional uses, including transfer of product in non-industrial settings
--------------------------------------	---

Environment	Use descriptors
CS01	

Worker	Use descriptors
CS02	
CS03	

Assessment method	MEASE
-------------------	-------

3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure:

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)	
Regional use tonnage:	≤ 80000 t/yr
Emission Days (days/year)	365

Technical and organisational conditions and measures	
Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
No emissions to water. In case of emissions to water, pH impact on the receiving water should be avoided, e.g. by neutralizing the effluent	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant	
Not applicable as there is no release to wastewater	

Exposure scenario

sulphur dioxide

Annex to the safety data sheet
Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions

3.2.2. Control of worker exposure:

Product (article) characteristics

Physical form of product

See section 9 of the SDS, No additional information

Concentration of substance in product

≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration

≤ 8 h/day

Covers frequency up to:

5 days/week

Technical and organisational conditions and measures

Handle product within a closed system

Drain down and flush system prior to equipment break-in or maintenance.

Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

Ensure operatives are trained to minimise exposure

Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374

Mandatory since the product is corrosive

Wear suitable working clothes. Chemical resistant safety shoes

Personal protection measures have to be applied in case of potential exposure only.

Use suitable eye protection. Wear suitable face shield

Personal protection measures have to be applied in case of potential exposure only.

Other conditions affecting workers exposure

Indoor or outdoor use

Exposure scenario

sulphur dioxide

Annex to the safety data sheet
Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

3.2.3. Control of worker exposure:

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 15 min/day

Technical and organisational conditions and measures	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374	Mandatory since the product is corrosive
Wear suitable working clothes. Chemical resistant safety shoes	Personal protection measures have to be applied in case of potential exposure only.
Use suitable eye protection. Wear suitable face shield	Personal protection measures have to be applied in case of potential exposure only.
Face mask with an ABEK1 filter offering an assigned protection factor of 30	

Other conditions affecting workers exposure	
Indoor or outdoor use	

3.3. Exposure estimation and reference to its source

3.3.1. Environmental release and exposure:

3.3.2. Worker exposure:

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	

Exposure scenario

sulphur dioxide

Annex to the safety data sheet
Reference number: D-SO2-113

CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Dermal - Acute - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Acute - Local - Inhalation	2.16 mg/m ³	Indoor or outdoor use, With LEV90%, With RPE95%	0.8

3.3.3. Worker exposure:

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Dermal - Acute - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Acute - Local - Inhalation	2.16 mg/m ³	Indoor or outdoor use, With LEV90%, With RPE95%	0.8

3.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

3.4.1. Environment

Guidance - Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
------------------------	---

3.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
-------------------	---

End of document